

ALLOY SHAFT AND COMPONENT SPECIFICATIONS

SIZE ¹³	SHAFT WEIGHT		SHAFT WEIGHT ¹⁰ @ 29"	SPINE @ 28" SPAN	STOCK LENGTH ³		UNI SYSTEM ⁵			NIBB POINT	ONE-PIECE BULLET POINT	RPS ⁷ INSERT ALUM.	RPS ⁷ POINT SIZE
	XX75 ¹	XX78 ²			CONVENTIONAL NOCK SIZE ⁴	UNI BUSHING ⁶	X NOCK BUSHING ⁶	SUPER UNI BUSHING ¹¹					
	Grains per lch		Grains	Deflection in Inches		Inches	Inches	Grains		Grains	Grains ⁸	Grains ⁸	
1816	9.3	—	270	0.733	30	9/32	8	4	—	63	74	12	9/32
1916	10.0	—	290	0.623	31	9/32	9	7	—	72	82	16	5/16
2013	9.0	—	261	0.610	32½	5/16	—	—	5	68	—	21	5/16
2016 (500)	10.6	—	307	0.531	32	—	—	—	4 ¹²	80	90	20	5/16
2018	12.3	—	357	0.464	32½	5/16	—	—	4	89	—	19	5/16
2020	13.5	—	392	0.426	33	5/16	—	—	—	64	—	18	5/16
2114 (510)	9.9	9.9	287	0.510	32½	—	(11)	—	7	78	100	25	5/16
2115	10.8	—	313	0.461	33	—	(11)	—	7	83	100	25	5/16
2117 (400)	12.0	12.1	348	0.407	33	5/16	—	—	7 ¹²	97	100	25	5/16
2212	—	8.8	255	0.505	32½	—	(13)	—	9	102 ⁹	100	31	11/32
2213 (460)	9.8	9.9	284	0.458	33½	—	(13)	—	9	88	100	30	11/32
2215	10.7	10.8	310	0.419	33	11/32	—	—	9	95	100	30	11/32
2216 (380)	12.0	12.1	348	0.376	33	11/32	—	—	9	98	100	29	11/32
2219	13.8	13.9	400	0.337	34	11/32	—	—	8	107	—	26	11/32
2312 (420)	—	9.5	276	0.423	33	—	(15)	—	11	99 ⁹	100	37	11/32
2314 (420)	10.7	10.8	310	0.391	33½	—	(14)	—	10	—	100	34	11/32
2315 (340)	11.7	11.8	339	0.342	34	—	—	—	11 ¹²	—	100	37	11/32
2317 (300)	13.3	13.4	386	0.297	34	—	—	—	11 ¹²	—	100	37	11/32
2412	—	9.7	281	0.400	34	—	(17)	—	12	110	100	40	11/32
2413 (360)	10.4	10.5	302	0.365	34	—	(17)	—	12	110	100	40	11/32
2512	—	10.3	299	0.321	34½	—	(20)	—	15	108 ⁹	100	52	11/32
2513 (310)	11.3	11.4	328	0.305	34½	—	(18)	—	14	—	100	48	11/32

— Indicates not available
 1 XX75 Realtree Hardwoods HD Green, Camo Hunter, GameGetter, Legacy.
 2 XX78 Super Slam.
 3 Length is approximately stock shaft length for each size.
 4 Nock size for conventional swaged nock taper.
 5 UNI—Universal Nock Installation System
 6 Prentthesis indicates smaller G Nock Uni Bushing size is available as an optional accessory.
 7 RPS = Replaceable point System with 8.32 ATA Standard thread.
 8 NIBB point grain weights are ± 0.5 grain. All other components are ± 1 grain.
 9 This NIBB point will provide approximately an 8% F.O.C. All other NIBB points are approximately 7% F.O.C. F.O.C. is Front-of-Center balance position on the arrow shaft.
 10 Whenever both XX75 and XX78 shaft models exist for any size, the weight shown represents the XX75 shaft model.
 11 Super UNI Bushing accepts Super Nock, 3D Super Nock and S Nock
 12 GameGetter composite bushing weight: 300 & 340 = 9 grains, 400 = 5 grains, 500 = 3 grains. 13 GameGetter and Super Slam Digital sizes indicated in parentheses.
 Notes: Shaft size 1716 uses BAR4; sizes 1813 and 1816 use BAR6; size 1916 uses BAR8 broadhead adapter rings